Schall-Ex® Jumbo III

- surface-mounted drop seal for extreme under-door gaps
- covers gaps up to 35mm
- robust stainless steel cover
- ideal for buildings where maintenance is limited
- suitable for acoustic and retrofit doors

APPLICATION

Usability	sound insulation, accessibility
Aplication area	exterior door, interior door
Door leaf material	timber, metal
Door type	hinged door, hinged gate
Door leaf	single leaf, double leaf
Opening direction	DIN L or R

TECHNICAL DATA

Carrier material	stainless steel
Surface	mill finish
Sealing profile material	self-extinguishing silicone
sealing profile colour	grey
actuator	screw
actuation	single

DIMENSIONS

Width	22 mm
Height	52.5 mm
Travel max.	35 mm
length min.-length max.	450 - 1700 mm
Standard lengths	708 mm, 833 mm, 958 mm, 1083 mm, 1208 mm
Cutback std. lengths	60 mm
Cutback information	min. delivery length cannot be cut back
fixed lengths available	yes

FIXING

Fixing	FS - surface mounted
installation	screw
Accessories incl.	5935
maintenance-free	yes
press plate required	yes
For retrofitting	yes

PERFORMANCE AND CERTIFICATION

EPD	EPD-ATD-36.1

Technische Änderungen vorbehalten / athmer 09.2026
athmer oHG / Sophienhammer / 59757 Arnsberg
T +49 2932 477-500 / info@athmer.com / **athmer.com**

Schall-Ex® Jumbo III

TECHNICAL DRAWING



INSTALLATION DRAWING



ART.NO.

1-157

Technische Änderungen vorbehalten / athmer 09.2026
athmer oHG / Sophienhammer / 59757 Arnsberg
T +49 2932 477-500 / info@athmer.com / **athmer.com**