Luftstop BD DIN L

- for sealing heights from 10 mm to 22 mm
- solid outer casing, with protective projection
- prevents damage to the door if it touches the floor
- DIN-R /-L specification necessary

APPLICATION

Usability	accessibility
Aplication area	interior door
Door leaf material	timber, metal
Door type	hinged door
Door leaf	single leaf, double leaf
Opening direction	DIN L

TECHNICAL DATA

Carrier material	aluminium
Surface	mill finish
Sealing profile material	PVC
sealing profile colour	grey
actuator	screw
actuation	single

DIMENSIONS

Width	30 mm
Height	10 mm
Travel max.	11 mm
length min.-length max.	200 - 1250 mm
Standard lengths	708 mm, 833 mm, 958 mm, 1083 mm, 1208 mm
Cutback std. lengths	125 mm
Cutback information	min. delivery length cannot be cut back
fixed lengths available	yes

FIXING

Fixing	screw fixed to the underside
installation	screw
Accessories incl.	5503
maintenance-free	yes
press plate required	yes
For retrofitting	yes

PERFORMANCE AND CERTIFICATION

EPD	EPD-ATD-36.1

Technische Änderungen vorbehalten / athmer 09.2026
athmer oHG / Sophienhammer / 59757 Arnsberg
T +49 2932 477-500 / info@athmer.com / **athmer.com**

Luftstop BD DIN L

TECHNICAL DRAWING



INSTALLATION DRAWING



ART.NO.

1-162

Technische Änderungen vorbehalten / athmer 09.2026
athmer oHG / Sophienhammer / 59757 Arnsberg
T +49 2932 477-500 / info@athmer.com / **athmer.com**